



SPECIFICATION

TIKKA T3 DELUXE



TIKKA T3 DELUXE based on a two locking lug T3 action. Bolt features springloaded plunger ejector and it can be easily stripped down for maintenance. Bolt is made of stainless steel.

The single-column detachable clip MAGAZINE holds 3-4 cartridges. Single-column 4-6-shot (depending on caliber) magazine is available as accessory (not in Short Mag calibers).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). Safety is two stage type and locks the trigger and the bolt handle when engaged. All models are available with a single-set trigger as option.

The walnut STOCK is oilfinished as standard and has a buttplate system where the length of pull is adjustable by means of spacers. Rosewood pistol grip cap and fore-end tip and T3-logo on the pistol grip cap. Straight stock features ambidextrous palm swell.

TIKKA T3 DELUXE is supplied without OPEN SIGHTS. Optionally available also with open sights with post bead where the rear sight is adjustable sideways and front sight in elevation. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard (Weaver) scope mount bases.

The free-floating BARREL is cold hammer-forged.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
T3	204 Ruger	12"	T3	1080 mm (42 1/2")
	222 Rem	14"	T3 Mag	1130 mm (44 1/2")
	223 Rem	8"	Barrel length	
	223 Rem	12"	T3	570 mm (22 7/16")
	22-250 Rem	14"	T3 Mag	620 mm (24 3/8")
	243 Win	10"	Weight	
	260 Rem	9"	T3	3.1 kg (6 13/16 lbs)
	7mm-08 Rem	9.5"	T3 Mag	3.2 kg (7 lbs)
	308 Win	11"	Cartridge capacity	
	338 Federal	10"	T3 204 Ruger, 222 Rem, 223 Rem	5 rounds (1 in chamber, 4 in clip magazine)
	25-06 Rem	10"	T3 other calibers	4 rounds (1 in chamber, 3 in clip magazine)
	6.5x55 SE	8"		
	270 Win	10"		
	7x64	10"		
	30-06 Sprg	11"		
	9.3x62	14"		
	7 mm Rem Mag	9.5"		
	300 Win Mag	11"		
	338 Win Mag	10"		
	270 Win Short Mag	10"		
300 Win Short Mag	11"			