



SPECIFICATION



TIKKA MASTER ALL-WEATHER



TIKKA MASTER ALL-WEATHER has a series of all-weather actions which are designated: Short action M595, Long action M695 incl. Magnum. Receiver, bolt and bolt handle are made of stainless steel. The detachable clip MAGAZINE holds 3 cartridges. 4-5-shot (depending on caliber) magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The STOCK is made of glass fiber reinforced copolymer polypropylene and has a buttplate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers. Features palm swell.

TIKKA MASTER ALL-WEATHER is supplied without OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard scope mount bases.

The free-floating, stainless steel BARREL is cold-hammerforged.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
M595	222 Rem	14"	M595	1070 mm (42 1/8")
	223 Rem	12"	M695	1080 mm (42 1/2")
	22-250 Rem	14"	M695 Mag	1130 mm (44 1/2")
	243 Win	10"	Barrel length	
	7mm-08 Rem	9.5"	M595	570 mm (22 7/16")
M695	308 Win	11"	M695	570 mm (22 7/16")
	25-06 Rem	10"	M695 Mag	620 mm (24 3/8")
	6.5x55 SE	8"	Weight	
	270 Win	10"	M595	3.2 kg (7 lbs)
	30-06 Sprg	11"	M695	3.3 kg (7 1/4 lbs)
M695 Mag	9.3x62	14"	M695 Mag	3.4 kg (7 1/2 lbs)
	7 mm Rem Mag	9.5"	Cartridge capacity	
	300 Win Mag	11"	M595	4 rounds (1 in chamber, 3 in clip magazine)
	338 Win Mag	10"	M695	4 rounds (1 in chamber, 3 in clip magazine)
			M695 Mag	4 rounds (1 in chamber, 3 in clip magaz.)



SPECIFICATION



TIKKA WHITETAIL HUNTER STAINLESS SYNTHETIC



TIKKA WHITETAIL HUNTER STAINLESS SYNTHETIC has a series of all-weather actions which are designated: Short action M595, Long action M695 incl. Magnum. Receiver, bolt and bolt handle are made of stainless steel.

The detachable clip MAGAZINE holds 3 cartridges. 4-5-shot (depending on caliber) magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs).

The STOCK is made of glass fiber reinforced copolymer polypropylene and has a buttplate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers. Features palm swell.

TIKKA WHITETAIL HUNTER STAINLESS SYNTHETIC is supplied without OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard scope mount bases.

The free-floating, stainless steel BARREL is cold-hammerforged.

Sling swivels standard.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length
M595	222 Rem	14"	M595 1070 mm (42 1/8")
	223 Rem	12"	M695 1080 mm (42 1/2")
	22-250 Rem	14"	M695 Mag 1130 mm (44 1/2")
	243 Win	10"	Barrel length
	7mm-08 Rem	9.5"	M595 570 mm (22 7/16")
M695	308 Win	11"	M695 570 mm (22 7/16")
	25-06 Rem	10"	M695 Mag 620 mm (24 3/8")
	6.5x55 SE *	8"	Weight
	270 Win	10"	M595 3.2 kg (7 lbs)
	30-06 Sprg	11"	M695 3.3 kg (7 1/4 lbs)
M695 Mag	9.3x62 *	14"	M695 Mag 3.4 kg (7 1/2 lbs)
	7 mm Rem Mag	9.5"	Cartridge capacity
	300 Win Mag	11"	M595 4 rounds (1 in chamber, 3 in clip magazine)
	338 Win Mag	10"	M695 4 rounds (1 in chamber, 3 in clip magazine)
	* Special order only		M695 Mag 4 rounds (1 in chamber, 3 in clip magaz.)