



SPECIFICATION



TIKKA MASTER BATTUE LIGHT



TIKKA MASTER BATTUE LIGHT has a series of actions which are designated: Short action M595, Long action M695 incl. Magnum. The receiver is lightened to reduce weight. Bolt handle is stainless steel. The detachable clip MAGAZINE holds 3 cartridges. 4-5-shot (depending on caliber) magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The lightened walnut STOCK is oilfinished and equipped with hard plastic butt plate as standard. Stock has also a buttplate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers. Features palm swell.

Special OPEN SIGHTS designed for snaphooting have adjustable rear sight (elevation). Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard scope mount bases.

The short, light, free-floating BARREL is cold-hammerforged.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
M595	308 Win	11"	M595	970 mm (38 3/16")
	7x64	10"	M695	980 mm (38 1/2")
M695	9.3x62	14"	M695 Mag	980 mm (38 1/2")
	M695 Mag	300 Win Mag	11"	
Cartridge capacity			Barrel length	
M595 4 rounds (1 in chamber, 3 in clip magazine)			M595	470 mm (18 1/2")
M695 4 rounds (1 in chamber, 3 in clip magazine)			M695	470 mm (18 1/2")
M695 Mag 4 rounds (1 in chamber, 3 in clip magaz.)			M695 Mag	470 mm (18 1/2")
			Weight	
			M595	3.0 kg (6 5/8 lbs)
			M695	3.1 kg (6 7/8 lbs)
			M695 Mag	3.1 kg (6 7/8 lbs)



SPECIAL ORDER ONLY



SPECIFICATION

TIKKA BATTUE LIGHT



TIKKA BATTUE LIGHT has a series of actions which are designated: Short action M595, Long action M695 incl. Magnum. The receiver is lightened to reduce weight. Bolt handle is stainless steel.

The detachable clip MAGAZINE holds 3 cartridges. 4-5-shot (depending on caliber) magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs).

The lightened walnut STOCK is oilfinished and equipped with hard plastic butt plate as standard. Stock has also a buttplate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers. Features palm swell.

Special OPEN SIGHTS designed for snaphooting have adjustable rear sight (elevation). Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard scope mount bases.

The short, light, free-floating BARREL is cold-hammerforged.

Sling swivels standard.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
M595	308 Win	11"	M595	970 mm (38 3/16")
	7x64	10"	M695	980 mm (38 1/2")
M695	9.3x62	14"	M695 Mag	980 mm (38 1/2")
M695 Mag	300 Win Mag	11"	Barrel length	
			M595	470 mm (18 1/2")
			M695	470 mm (18 1/2")
			M695 Mag	470 mm (18 1/2")
Cartridge capacity			Weight	
M595 4 rounds (1 in chamber, 3 in clip magazine)			M595	3.0 kg (6 5/8 lbs)
M695 4 rounds (1 in chamber, 3 in clip magazine)			M695	3.1 kg (6 7/8 lbs)
M695 Mag 4 rounds (1 in chamber, 3 in clip magaz.)			M695 Mag	3.1 kg (6 7/8 lbs)