



# SPECIFICATION



## TIKKA MASTER CONTINENTAL



TIKKA MASTER CONTINENTAL has a series of actions which are designated: Short action M595, Long action M695 incl. Magnum. Bolt handle is stainless steel.

The detachable clip MAGAZINE holds 4-6 cartridges, depending on caliber. 3-shot extra magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The walnut STOCK with extra wide fore-end is oilfinished as standard and has a buttplate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers. Matte-lacquered stocks are also available. Features palm swell.

TIKKA MASTER CONTINENTAL is supplied without OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard scope mount bases.

The free-floating BARREL is cold-hammerforged. On special order rifles can also be supplied with stainless steel barrel.

### TECHNICAL DATA

| Action          | caliber      | rate of twist | Overall length                                       |
|-----------------|--------------|---------------|--|
| <b>M595</b>     | 17 Rem       | 10"           | M595 1110 mm (43 3/4")                               |
|                 | 222 Rem      | 14"           | M695 1120 mm (44")                                   |
|                 | 223 Rem      | 12"           | M695 Mag 1120 mm (44")                               |
|                 | 22-250 Rem   | 14"           | <b>Barrel length</b>                                 |
|                 | 243 Win      | 10"           | M595 600 mm (23 3/8")                                |
|                 | 7mm-08 Rem   | 9.5"          | M695 600 mm (23 3/8")                                |
|                 | 308 Win      | 11"           | M695 Mag 600 mm (23 3/8")                            |
| <b>M695</b>     | 25-06 Rem    | 10"           | <b>Weight</b>  |
|                 | 6.5x55 SE    | 8"            | M595 3.7 kg (8 1/8 lbs)                              |
|                 | 270 Win      | 10"           | M695 3.8 kg (8 3/8 lbs)                              |
|                 | 7x64         | 10"           | M695 Mag 3.8 kg (8 3/8 lbs)                          |
|                 | 30-06 Sprg   | 11"           | <b>Cartridge capacity</b>                            |
| <b>M695 Mag</b> | 9.3x62       | 14"           | M595 6 rounds (1 in chamber, 5 in clip magazine)     |
|                 | 7 mm Rem Mag | 9.5"          | M695 6 rounds (1 in chamber, 5 in clip magazine)     |
|                 | 300 Win Mag  | 11"           | M695 Mag 5 rounds (1 in chamber, 4 in clip magazine) |
|                 | 338 Win Mag  | 10"           |  |



# SPECIFICATION



## TIKKA CONTINENTAL



TIKKA CONTINENTAL has a series of actions which are designated: Short action M595, Long action M695 incl. Magnum. Bolt handle is stainless steel.

The detachable clip MAGAZINE holds 4-6 cartridges, depending on caliber. 3-shot extra magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs).

The walnut STOCK with extra wide fore-end is mattelaquered and has a buttplate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers. Features palm swell.

TIKKA CONTINENTAL is supplied without OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard scope mount bases.

The free-floating BARREL is cold-hammerforged. On special order rifles can also be supplied with stainless steel barrel.

Sling swivels standard.

### TECHNICAL DATA

| Action          | caliber      | rate of twist | Overall length            |   |
|-----------------|--------------|---------------|---------------------------|---|
| <b>M595</b>     | 17 Rem       | 10"           | M595                      | 1110 mm (43 3/4")                           |
|                 | 222 Rem *    | 14"           | M695                      | 1120 mm (44")                               |
|                 | 223 Rem      | 12"           | M695 Mag                  | 1120 mm (44")                               |
|                 | 22-250 Rem   | 14"           | <b>Barrel length</b>      |   |
|                 | 243 Win      | 10"           | M595                      | 600 mm (23 3/8")                            |
|                 | 7mm-08 Rem   | 9.5"          | M695                      | 600 mm (23 3/8")                            |
|                 | 308 Win      | 11"           | M695 Mag                  | 600 mm (23 3/8")                            |
| <b>M695</b>     | 25-06 Rem    | 10"           | <b>Weight</b>             |   |
|                 | 6.5x55 SE *  | 8"            | M595                      | 3.7 kg (8 1/8 lbs)                          |
|                 | 270 Win      | 10"           | M695                      | 3.8 kg (8 3/8 lbs)                          |
|                 | 7x64 *       | 10"           | M695 Mag                  | 3.8 kg (8 3/8 lbs)                          |
|                 | 30-06 Sprg   | 11"           | <b>Cartridge capacity</b> |   |
| <b>M695 Mag</b> | 9.3x62 *     | 14"           | M595                      | 6 rounds (1 in chamber, 5 in clip magazine) |
|                 | 7 mm Rem Mag | 9.5"          | M695                      | 6 rounds (1 in chamber, 5 in clip magazine) |
|                 | 300 Win Mag  | 11"           | M695 Mag                  | 5 rounds (1 in chamber, 4 in clip magazine) |
|                 | 338 Win Mag  | 10"           |                           |   |

\* Special order only