

SPECIFICATION



TIKKA MASTER



TIKKA MASTER has a series of actions which are designated: Short action M595, Long action M695 incl. Magnum. Models are also available in left hand (LH) version. Bolt handle is stainless steel.

The detachable clip MAGAZINE holds 3 cartridges. 4-6-shot (depending on caliber) magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The walnut STOCK is oilfinished as standard and has a buttplate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers. Mattelacquered stocks are also available. Features palm swell.

OPEN SIGHTS with post bead are adjustable in sideways. All models are available also without sights. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard scope mount bases.

The free-floating BARREL is cold-hammerforged.

TECHNICAL DATA

m (42 1/8")		
m (42 1/2")		
m (44 1/2")		
n (22 7/16")		
n (22 7/16")		
n (24 3/8")		
` ,		
(7 lbs)		
7 1/4 lbs)		
7 1/2 lbs)		
1 1/2 150)		
Cartridge capacity M595 4 rounds (1 in chamber, 3 in clip magazine) M695 4 rounds (1 in chamber, 3 in clip magazine) M695 Mag 4 rounds (1 in chamber, 3 in clip magaz.)		
		יו יו



SPECIFICATION



TIKKA WHITETAIL HUNTER



TIKKA WHITETAIL HUNTER has a series of actions which are designated: Short action M595, Long action M695 incl. Magnum. Models are also available in left hand (LH) version. Bolt handle is stainless steel. The detachable clip MAGAZINE holds 3 cartridges. 4-6-shot (depending on caliber) magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs).

The walnut STOCK is mattlaquered and has a buttplate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers. Features palm swell.

TIKKA WHITETAIL HUNTER is supplied WITHOUT OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard scope mount bases.

The free-floating BARREL is cold-hammerforged.

Sling swivels standard.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
	222 Rem *	14"	M595	1070 mm (42 1/8")
	223 Rem	12"	M695	1080 mm (42 1/2")
M595	22-250 Rem	14"	M695 Mag	1130 mm (44 1/2")
	243 Win	10"	Barrel length	
	7mm-08 Rem	9.5"	M595	570 mm (22 7/16")
	308 Win	11"	M695	570 mm (22 7/16")
	25-06 Rem	10"	M695 Mag	620 mm (24 3/8")
M695	6.5x55 SE *	8"	Weight	,
	270 Win	10"	M595	3.2 kg (7 lbs)
	7x64 *	10"	M695	3.3 kg (7 1/4 lbs)
	30-06 Sprg	11"	M695 Mag	3.4 kg (7 1/2 lbs)
	9.3x62 *	14"	Cartridge capac	3 ,
•	7 mm Rem Ma	ıg 9.5"	M595 4 rounds (1 in chamber, 3 in clip magazine) M695 4 rounds (1 in chamber, 3 in clip magazine) M695 Mag 4 rounds (1 in chamber, 3 in clip magaz.)	
M695 Mag	300 Win Mag	11"		
	338 Win Mag	10"		
	* Special orde	r only	wides way 4 founds (Till Chamber, 5 in clip magaz.)