



SPECIFICATION



TIKKA MASTER PRO



TIKKA MASTER PRO has a series of actions which are designated: Short action M595 and Long action M695 incl. Magnum. Bolt handle is stainless steel.

The detachable clip MAGAZINE holds 3 cartridges. 4-6-shot (depending on caliber) magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs).

The walnut STOCK is oilfinished and has a butt plate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers and in height with an adjustable cheek piece. Features palm swell.

OPEN SIGHTS with post bead are adjustable in windage. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard scope mount bases.

The free-floating BARREL is cold-hammerforged.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
M595	222 Rem	14"	M595	1070 mm (42 1/8")
	223 Rem	12"	M695	1080 mm (42 1/2")
	22-250 Rem	14"	M695 Mag	1130 mm (44 1/2")
	243 Win	10"	Barrel length	
	7mm-08 Rem	9.5"	M595	570 mm (22 7/16")
	308 Win	11"	M695	570 mm (22 7/16")
M695	25-06 Rem	10"	M695 Mag	620 mm (24 3/8")
	6.5x55 SE	8"	Weight	
	270 Win	10"	M595	3.2 kg (7 lbs)
	7x64	10"	M695	3.3 kg (7 1/4 lbs)
	30-06 Sprg	11"	M695 Mag	3.4 kg (7 1/2 lbs)
M695 Mag	9.3x62	14"	Cartridge capacity	
	7 mm Rem Mag	9.5"	M595	4 rounds (1 in chamber, 3 in clip magazine)
	300 Win Mag	11"	M695	4 rounds (1 in chamber, 3 in clip magazine)
	338 Win Mag	10"	M695 Mag	4 rounds (1 in chamber, 3 in clip magaz.)



SPECIAL ORDER ONLY



SPECIFICATION

TIKKA WHITETAIL HUNTER PRO



TIKKA WHITETAIL HUNTER PRO has a series of actions which are designated: Short action M595 and Long action M695 incl. Magnum. Bolt handle is stainless steel.

The detachable clip MAGAZINE holds 3 cartridges. 4-6-shot (depending on caliber) magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs).

The walnut STOCK is oilfinished and has a butt plate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers and in height with an adjustable cheek piece. Features palm swell.

OPEN SIGHTS with post bead are adjustable in windage. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard scope mount bases.

The free-floating BARREL is cold-hammerforged.

Sling swivels standard.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
M595	222 Rem	14"	M595	1070 mm (42 1/8")
	223 Rem	12"	M695	1080 mm (42 1/2")
	22-250 Rem	14"	M695 Mag	1130 mm (44 1/2")
	243 Win	10"	Barrel length	
	7mm-08 Rem	9.5"	M595	570 mm (22 7/16")
M695	308 Win	11"	M695	570 mm (22 7/16")
	25-06 Rem	10"	M695 Mag	620 mm (24 3/8")
	6.5x55 SE	8"	Weight	
	270 Win	10"	M595	3.2 kg (7 lbs)
	7x64	10"	M695	3.3 kg (7 1/4 lbs)
M695 Mag	30-06 Sprg	11"	M695 Mag	3.4 kg (7 1/2 lbs)
	9.3x62	14"	Cartridge capacity	
	7 mm Rem Mag	9.5"	M595	4 rounds (1 in chamber, 3 in clip magazine)
	300 Win Mag	11"	M695	4 rounds (1 in chamber, 3 in clip magazine)
	338 Win Mag	10"	M695 Mag	4 rounds (1 in chamber, 3 in clip magaz.)